



US008406802B2

(12) **United States Patent**
Tiedemann, Jr.

(10) **Patent No.:** **US 8,406,802 B2**
(45) **Date of Patent:** **Mar. 26, 2013**

(54) **METHODS AND APPARATUSES FOR FAST POWER CONTROL OF SIGNALS TRANSMITTED ON A MULTIPLE ACCESS CHANNEL**

(75) Inventor: **Edward G. Tiedemann, Jr.**, San Diego, CA (US)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1016 days.

(21) Appl. No.: **11/857,416**

(22) Filed: **Sep. 18, 2007**

(65) **Prior Publication Data**
US 2008/0102878 A1 May 1, 2008

Related U.S. Application Data

(63) Continuation of application No. 09/811,221, filed on Mar. 16, 2001, now Pat. No. 7,286,499, and a continuation-in-part of application No. 09/113,721, filed on Jul. 10, 1998, now Pat. No. 6,275,478.

(51) **Int. Cl.**
H04W 52/04 (2009.01)
H04B 7/00 (2006.01)

(52) **U.S. Cl.** **455/522**; 455/69; 455/13.4; 455/67.11

(58) **Field of Classification Search** 455/522, 455/69, 127.1, 13.4, 517, 68, 67.11; 370/318, 370/317, 315, 322, 328, 329
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,901,307 A 2/1990 Gilhousen et al.
5,056,109 A 10/1991 Gilhousen et al.

5,101,501 A	3/1992	Gilhousen et al.	
5,265,119 A	11/1993	Gilhousen et al.	
5,345,598 A *	9/1994	Dent	455/522
5,564,075 A	10/1996	Gourgue	
5,590,409 A	12/1996	Sawahashi et al.	
5,604,730 A	2/1997	Tiedemann, Jr.	
5,621,723 A	4/1997	Walton et al.	
5,751,763 A *	5/1998	Bruckert	375/141
5,806,003 A	9/1998	Jolma et al.	
5,881,368 A	3/1999	Grob et al.	
5,893,036 A	4/1999	Trandai et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0847147	6/1998
WO	WO9321700	10/1993

(Continued)

OTHER PUBLICATIONS

European Search Report—EP07115709, Search Authority—Munich, Jan. 21, 2009.

(Continued)

Primary Examiner — John J Lee

(74) *Attorney, Agent, or Firm* — Liem T. Do

(57) **ABSTRACT**

A method and apparatus for controlling the transmission of signals from one or more of a plurality of mobile stations to a base station on a plurality of M multiple access channels is described. A power control information packet formed from a plurality of power control bits is transmitted from the base station to the one or more mobile stations. Each of the power control bits in the power control information packet has a position that is mapped to a selected access channel and to a time offset within the selected access channel. The power control information packet is received at a first mobile station. A message is then transmitted from the first mobile station to the base station on a first access channel and at a first time offset associated with the first access channel.

16 Claims, 13 Drawing Sheets

